



Outdoor 4G LTE Wireless Router with 12V DC Out

WI-LTE115-O

Overview

WI-LTE115-O is an outdoor 4G LTE wireless router with DC Out, plug-in card automatic networking, monitoring anytime and anywhere and is suitable for monitoring scenarios such as rural areas, ranches, and scenic spots that are inconvenient to handle broadband. Support IP65 dustproof and waterproof, deal with various weather conditions, built-in 1*100Mbps interfaces, convenient for IPC access, external LTE antenna, 4G signal is stronger.

Features

4G LTE

The ideal 4G LTE Router with up to 150Mbps download speed and 50Mbps upload speed and is backward compatible with 4G/3G networks.

Plug and Play

No configuration is needed simply plug and play.

Ideal for Outdoor Environment

IP65 weatherproof enclosure for outdoor Wi-Fi applications.

Cloud Management

The free cloud management platform simplifies a lot of equipment management time and reduces network supervision costs for network administrators.

SD-LAN

Realize remote intranet intercommunication, so that the camera data in remote areas can be sent back to the monitoring room.

DC Out

The DC Out Port is designed to deliver power directly to the camera. It greatly facilitates monitoring networking solutions and application scenarios.







Specifications

Products	WI-LTE115-O	
Hardware Version	V2	
Interface	(1)10/100M Base-T Ethernet Port	
Signal Rate	300 Mbps at 2.4 GHz	
Wi-Fi Antenna	5dBi	
Power Supply	1 x DC 12V/1.5A Input	
DC Out	1 x DC 12V/1A Output	
Power Consumption	<5W	
External Buttons	Reset Button (long press for 8 seconds to restore the factory default configuration)	
Transmit Power	20dBm	
LTE/3G/2G Bands	EU: LTE FDD: B1/B3/B5/B7/B8/B20/B28 LTE TDD: B38/ B40/B41 WCDMA: B1/B5/B8 GSM: B3/B8 CN: LTE FDD: B1/B3/B5/B8 LTE TDD: B34/B38/B39/B40/B41 WCDMA: B1/B5/B8 GSM: B3/B8 LA: LTE FDD: B1/B2/B3/B4/B5/B7/B8/B28/B66 LTE TDD: B40 WCDMA: B1/B2/B3/B4/B5/B8 GSM: B2/B3/ B5/B8	
LTE Category	Cat 4	
Dimensions	152mm x 78mm x 35mm	
Environment	Working Temp: -40~ 70°C Storage Temp: -40~85°C Working Humidity: 10%~95% non-condensing	
Software Features	3G/4G Router	
	DHCP Server, Client	
	NAT Rules	
	Port Forwards	
	Static Routes	
	DDNS	
	OpenVPN	
	SD-LAN	
	Cloud Management	

Package Content

Welcome to order our products. After purchasing, you will receive:

Items	Quantity
WI-LTE115-O	1 pcs
Pole Mounting Strap	2 pcs
DC Adapter	1 pcs
DC female-to-female power extension cord	1 pcs
Quick Installation Guide	1 pcs



Wireless-Tek Technology Limited

Address: Biaofang Technology Building 402, Bao'an street,

Baoan District, Shenzhen City, Guangdong, China

Website:www.wireless-tek.com

Tel:86-0755-32811290

Email:sales@wireless-tek.com

Technical Support:tech@wireless-tek.com







Cloud Management



Company Website