

Outdoor 4G LTE wireless Router with PoE Out

WI-LTE117-O

Overview

WI-LTE117-O is an outdoor 4G LTE wireless router with PoE Out, plug-in card automatic networking, monitoring anytime and anywhere, and is suitable for monitoring scenarios such as rural areas, ranches, and scenic spots that are inconvenient to handle broadband. Support IP65 dustproof and waterproof, deal with various weather conditions, built-in 2*100Mbps PoE interfaces, convenient for IPC access, external LTE dual antenna, 4G signal is stronger.

Features

4G LTE

The ideal 4G LTE Router with up to 150Mbps download speed and 50Mbps upload speed and is backward compatible with 4G/3G networks.

Plug and Play

No configuration is needed simply plug and play.

Ideal for Outdoor Environment

IP65 weatherproof enclosure for outdoor Wi-Fi applications.

Cloud Management

The free cloud management platform simplifies a lot of equipment management time and reduces network supervision costs for network administrators.

SD-LAN

Realize remote intranet intercommunication, so that the camera data in remote areas can be sent back to the monitoring room.

OpenVPN

Support OpenVPN, which enables employees to connect remotely to their main office as securely as in the office.

WAN Connection Backup

Works as a router to provide a backup internet connection.

PoE Out

Multiple PoE Out Port designs can directly use a network cable to connect the camera and transmit data and power to the camera at the same time. It greatly facilitates monitoring networking solutions and application scenarios.



Specifications

| Products | WI-LTE117-O |
|-------------------------|--|
| Hardware Version | |
| Interface | (2)10/100M Base-T Ethernet Ports |
| Signal Rate | 300 Mbps at 2.4 GHz |
| Wi-Fi Antenna | 5dBi |
| Power Supply | 48-52V DC/1A |
| Power Consumption | < 5W |
| External Buttons | reset button (long press for 8 seconds to restore the factory default configuration) |
| Transmit Power | 20dBm |
| LTE/3G/2G Bands | EU: LTE FDD: B1/B3/B5/B7/B8/B20/B28 LTE TDD: B38/ B40/B41 WCDMA: B1/B5/B8 GSM: B3/B8 CN: LTE FDD: B1/B3/B5/B8 LTE TDD: B34/B38/B39/B40/B41 WCDMA: B1/B5/B8 GSM: B3/B8 |
| LTE Category | Cat 4 |
| 4G/ETH Failover | Yes |
| Dimensions | 152mm x 78mm x 35mm |
| Environment | Working Temp: -40°C~70°C Storage Temp: -40°C~85°C Working Humidity: 10%~95% non-condensing |
| Software Features | 3G/4G Router, Wireless Router, Eth-First Router, 4G-First Router |
| | DHCP Server, Client |
| | NAT Rules, Port Forwards |
| | Static Routes |
| | DDNS |
| | OpenVPN |
| | SD-LAN |
| | Cloud management |



Wireless-Tek Technology Limited

Address: Room 402 4F, BiaoFan Technology Building, Bao'An Avenue, FuYong Town, Bao'An district, ShenZhen

Website: www.wireless-tek.com

Tel: 86-0755-32811290

Email: sales@wireless-tek.com

Technical Support: tech@wireless-tek.com



Technical Support



Cloud Management



Company Website